

# Impact of external screening on the valence and core-level photoelectron spectra of one-layer WS<sub>2</sub>

Alex Boehm,<sup>1</sup> Christopher M. Smyth,<sup>1</sup> Andrew R. Kim,<sup>1</sup> Don Bethke,<sup>1</sup> Tzu-Ming Lu,<sup>1</sup>  
Jose J. Fonseca,<sup>2</sup> Jeremy T. Robinson,<sup>2</sup> Taisuke Ohta<sup>1</sup>

<sup>1</sup> Sandia National Laboratories, Albuquerque, NM 87185, United States

<sup>2</sup> U.S. Naval Research Laboratory, Washington, DC, 20375, United States

In an effectively-screened environment, transition metal dichalcogenides (TMDs) rearrange their charge carriers to screen the added charges, and reduce the electronic band gap. Consequently, when interfaced with dissimilar materials, a sheet of TMD would change its band gap adapted to its local external screening environment. Similarly, a well-screened environment stabilizes photo-holes or core-holes created in the photoemission process and, in turn, boosts the kinetic energy of photoelectrons resulting in the apparent smaller binding energy. Complication arises when determining the electronic band alignment of TMDs using photoelectron spectroscopy since the screening influences the material property of interest as well as its assessment approach concurrently. Using a sample that contains areas of suspended and gold-supported one-layer WS<sub>2</sub>, we show how the electronic states of WS<sub>2</sub> under the contrasting effective or ineffective external screening environment align at the built-in junction. The photoelectron spectra point to the breakdown of rigid shifts between the valence states and core-levels with the core-levels shifting more than twice as much as the valence states. Additionally, effectively-screened WS<sub>2</sub> displays a valence state with a substantially larger photoemission linewidth than ineffectively-screened suspended WS<sub>2</sub>. Altogether, our result provides key insights into how the local variation of the external screening environment creates essentially a heterojunction within a layer of WS<sub>2</sub>, and whether commonly accepted photoelectron spectroscopy practices hold when examining the electronic structures of one-layer TMDs.

The work was supported by the Laboratory Directed Research and Development program at Sandia National Laboratories and Base Programs and the Nanoscience Institute at the Naval Research Laboratory via the Office of Naval Research. A.R.K. acknowledges support from the U.S. Department of Energy, Office of Science, Division of Materials Sciences and Engineering (grant BES 20-017574). Samples were fabricated, in part, at the Center for Integrated Nanotechnologies, an Office of Science User Facility operated for the US Department of Energy, Office of Science. Sandia National Laboratories is a multi-mission laboratory managed and operated by National Technology and Engineering Solutions of Sandia, LLC., a wholly-owned subsidiary of Honeywell International, Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525. Any subjective views or opinions that might be expressed in the paper do not necessarily represent the views of the U.S. Department of Energy or the United States Government.

<sup>+</sup> Author for correspondence: tohta@sandia.gov